

AN 702 webrax

Product

AN 702 is Hermes Abrasives non-woven reinforced conditioning product. The non-woven, nylon construction provides the consistent surfaces required in decorative finishing applications as well as being effective in cleaning and light deburring operations.

Construction

Abrasive Grain: Aluminum Oxide
Backing: Scrim back
Bond: Full Resin
Grit Range: P100, P180, P280, P320, P400
Maximum manufactured width: 62"

Workpieces

Hardware, jewelry, stainless steel sinks, auto and appliance trim, cookware, cutlery, tubing, plated plastics, restaurant and dairy equipment, turbine blades, metal sheets and coils.

Applications

Decorative finishing, cleaning and conditioning of metal surfaces. Light deburring, satin finishing and weld blending of both ferrous and non-ferrous metals including stainless steel, aluminum, carbon steel, brass, gold and silver.

Machines

Finished sanding achieved on back-stand, bench mounted, stroke sanders, pneumatic sleeve and wide belt equipment.

Forms

Narrow belts

-FE 40

Dimensions available:
-widths up to 12"
-length depends on the sanding machine
Joints: UBN (001), EB 32 (032), EB 38 (038)



Wide belts

-FE 41

Dimensions available:
-widths up to 12 1/4" and wider
-length depends on the sanding machine
Joints: EB 32 (032)



Type #: 70200

PB32

Advantages of AN 702 webrax

1. Resistance of loading and clogging
2. Reduced heat generation during operation
3. Improves surface quality
4. Flexible to conform to contoured as well as flat surfaces
5. Can be used dry or with lubricants or coolants
6. Does not require a "break-in" period
7. Will not contaminate or oxidize workpieces
8. May be run at conventional belt speeds

Distributed by:



Hermes Abrasives Ltd.

P.O. Box 2389
Virginia Beach, VA 23450

524 Viking Drive
Virginia Beach, VA 23452

Phone 757-486-6623
Toll Free Phone 1-800-464-8314
www.hermesabrasives.com

Fax 757-431-2370
Toll free fax 1-800-243-7637